

IN THE CLAIMS:

Please amend claim 1 follows:

1. (Currently Amended) A head slider for a magnetic disk lifted above the magnetic disk by airflow generated by rotation of the magnetic disk, said head slider comprising:

a disk-facing surface having an air bearing surface raised from said disk-facing surface and a ~~recessed-portion~~ recessed from said disk-facing surface located behind said air bearing surface when viewed in a direction of the airflow,

an airflow guide part located in said recessed portion and guiding the airflow along the disk-facing surface of said head slider toward sides of the disk-facing surface,

wherein the air flow guide part includes a first guide groove formed between both sides of the disk-facing surface.

2. (Original) The head slider as claimed in claim 1, wherein the airflow guide part is formed to extend in directions each inclined at an angle with respect to a flow direction of the airflow.

3. (Original) The head slider as claimed in claim 1, wherein the airflow guide part includes a capturing part that captures dust included in the airflow.

4. (Original) The head slider as claimed in claim 1, wherein the airflow guide part comprises:

a first guide part formed to extend from the vicinity of the center of the disk-facing surface to both sides of the disk-facing surface; and

a pair of second guide parts formed on opposing side surfaces of said head slider and continuing with said first guide part.

5. (Original) The head slider as claimed in claim 4, wherein the first and second guide parts are formed to extend in respective directions each inclined at an angle with respect to a flow direction of the airflow.

6. (Original) The head slider as claimed in claim 4, wherein one of the first and second guide parts includes a capturing part that captures dust included in the airflow.

7. (Previously Presented) The head slider as claimed in claim 1, wherein:

said first guide groove is formed to extend from the vicinity of the center of the disk-facing surface toward both sides of the disk-facing surface; and

a pair of second guide grooves are formed on opposing side surfaces of said head slider and communicating with said first guide groove.

8. (Original) The head slider as claimed in claim 7, wherein one of the first and second guide grooves includes a capturing groove that captures dust included in the airflow, and the capturing groove is formed deeper than the first and second guide grooves.

9. (Original) The head slider as claimed in claim 7, wherein, in the first guide groove, an inflow-side wall along which the airflow flowing along the disk-facing surface enters the first guide groove is an inclined surface, and an outflow-side wall along which the airflow flowing along the disk-facing surface is discharged is a vertical surface.

10. (Previously Presented) The head slider as claimed in claim 1, wherein the disk facing surface includes a pair of front pads, located in front of and adjacent to said recessed portion when viewed in a direction of the airflow, and further wherein the airflow is guided between said front pads toward said airflow guide part.